AQUASPORTS MARINE

Phone: 08 9250 3339

Email: info@aquasportsmarine.com.au

Website:



Boat Details

Price POA **Boat Brand** Mercruiser Bravo One (Sterndrive) Model Length 0.00

2016 Year Category **Boat Engines and Outboards**

Hull Style Other **Hull Type** Other **Power Type** Engine/Motor Stock Number

Western Australia Condition State New Mercruiser

Suburb **MIDVALE Engine Make**

Description

Mercruiser Bravo One Sterndrive - For more than 45 years the word "MerCruiser" has meant sterndrive performance. Choose from more than 20 unique drive systems such as our Alpha One, the most popular sterndrive in the world, or our brawny Bravo Series drives. MerCruiser has the perfect drive system for you and your boat. Great Performance Starts with Heart. Bravo! Single, twin, triple applications over 100 mph for gas engines up to 600 hp

Maximum Power Capacity400 HP (295 kW)

Lower Unit DesignPerformance Torpedo

Maximum Propeller Diameter1 X 16"

Water Inlet LocationDWP - Torpedo and Strut

Clutch TypeHigh-Strength Smooth-Shift Cone Clutch with F-N-R

Available Gear Ratios 1.36, 1.50, 1.65:1

Counter-RotationStandard

Upper Unit Gear SetPrecision Shimmed Assembly with Near-Net Forged Helical Gears

Lower Unit Gear SetPrecision Shimmed Assembly Forged Bevel Gears with Twin Counter Rotating Propshafts for Bravo Three

Propshaft MaterialHeat-Treated Stainless Steel

Standard Exhaust OutletThrough Propeller

Required Propeller HubFlo-Torg II Hub

Recommended LubricantMercury High-Performance Gear Lube

Monitoring SystemEngine-Mounted Lube Monitor w/Audio Warning or Engine Guardian®

Corrosion Warranty3-Year, Limited

Housing ConstructionCorrosion Resistant XK 360 Aluminum Low-Copper Alloy

Corrosion ProtectionTri-Paint, Anodes & MerCathode® Electronic Corrosion Prevention

Anode TypeUltra-Pure Aluminum Anodes or Magnesium Anode Kit

Speedometer Pick-upIntegrated Into Lower Housing, Digital Output Optional

Steering SystemSingle Cylinder Power Steering with Anti-Feedback

Steering Range56° Range Stop to Stop, Digital Output Optional

U-Joint TypePermalube® Virtually Maintenance-Free

Power Trim SystemTwin-Cylinder Hydraulic Featuring Power Trim XD® Kick-up Return

Typical Trim Range-5° to 11°

Trim Limit SwitchAdjustable Limit Analog or Digital - Engine Dependant

Trailer Limit46°

Trim Hinge Pin DesignPermanently Lubricated - No Maintenance Required

Hydraulic Trim LinesStainless Steel Braided Armor

Drive CouplerGreaseable From Inside Boat

Drive Weight125 lbs. (57 kg)

Features

Horse Power (hp) 400

Engine Details

Engine Make Mercruiser Horse Power 435