



Phone: 08 9250 3339
Email: info@aquasportsmarine.com.au
Website:

Boat Details

Price	POA	Boat Brand	Mercruiser
Model	Bravo Three (Sterndrive)	Length	0.00
Year	2016	Category	Boat Engines and Outboards
Hull Style	Other	Hull Type	Other
Power Type	Engine/Motor	Stock Number	0
Condition	New	State	Western Australia
Suburb	MIDVALE	Engine Make	Mercruiser

Description

Mercruiser Bravo Three Sterndrive - Efficient, easy to manoeuvre and an exciting performer, Bravo Three drives represent the complete package. * Single or twin installation for engines up to 525hp * Counter-rotating propellers provide agile handling. * Ultra-pure aluminium anodes and Mercury-exclusive MerCathode help prevent galvanic corrosion. *Excellent reverse handling and smooth, best-in-class shifting.

Maximum Power Capacity400 HP (295 kW)

Lower Unit DesignExtended Length Strut

Maximum Propeller Diameter2 X 16"

Water Inlet LocationStrut

Clutch TypeHigh-Strength Smooth-Shift Cone Clutch with F-N-R

Available Gear Ratios1.81, 2.00, 2.20, 2.43:1

Counter-RotationTwin Prop

Upper Unit Gear SetPrecision Shimmed Assembly with Near-Net Forged Helical Gears

Lower Unit Gear SetPrecision Shimmed Assembly Forged Bevel Gears with Twin Counter Rotating Propshafts for Bravo Three

Propshaft MaterialHeat-Treated Stainless Steel

Standard Exhaust OutletThrough Propeller

Required Propeller HubNone for Bravo Three

Recommended LubricantMercury High-Performance Gear Lube

Monitoring SystemEngine-Mounted Lube Monitor w/Audio Warning or Engine Guardian®

Corrosion Warranty3-Year, Limited

Housing ConstructionCorrosion Resistant XK 360 Aluminum Low-Copper Alloy

Corrosion ProtectionTri-Paint, Anodes & MerCathode® Electronic Corrosion Prevention

Anode TypeUltra-Pure Aluminum Anodes or Magnesium Anode Kit

Speedometer Pick-upIntegrated Into Lower Housing, Digital Output Optional

Steering SystemSingle Cylinder Power Steering with Anti-Feedback

Steering Range56° Range Stop to Stop, Digital Output Optional

U-Joint TypePermalube® Virtually Maintenance-Free

Power Trim SystemTwin-Cylinder Hydraulic Featuring Power Trim XD® Kick-up Return

Typical Trim Range-2° to 14°

Trim Limit SwitchAdjustable Limit Analog or Digital - Engine Dependant

Trailer Limit51°

Trim Hinge Pin DesignPermanently Lubricated - No Maintenance Required

Hydraulic Trim LinesStainless Steel Braided Armor

Drive CouplerGreaseable From Inside Boat

Drive Weight148 lbs. (67 kg)

Features

Horse Power (hp)	400
------------------	-----

Engine Details

Engine Make	Mercruiser
Horse Power	525